




ivNow[®]
individual warming pods



warming cabinets
blanket | elite series | fluid | combination



800.822.3501 • FAX 360.696.1700 • www.pedigo-usa.com



4000 SE Columbia Way • Vancouver, Washington 98661

10/18 MM-76



blanket warming cabinets

Warmers feature solid door and temperature control.



Shelf Dimensions
17"W x 27"D x 12¼"H

P-2010-TC Transfer Cart

OVERALL SIZE

23¼"W x 32¼"D x 43"H

FEATURES

- Ergonomic Push/Pull handles
- 4" casters with brake & swivel lock

- Stainless steel
- 300 lbs. total weight capacity at 100 lbs. per shelf
- Compatible with the P-2010-S and P-2110 warming cabinets



P-2010-S

OVERALL SIZE

16½"W x 25¼"D x 21½"H

COMPARTMENT SIZE

- 2.3 cubic ft.
- 13¼"W x 21¾"D x 14"H

- Ideal for countertop use
- Temp Range: 98°F - 200°F
- Unit can be stacked

NEW!



P-2012

OVERALL SIZE

18½"W x 23½"D x 22"H

COMPARTMENT SIZE

- 2.5 cubic ft.
- 15½"W x 18¾"D x 15¼"H

- Ideal for countertop use
- Unit can be stacked (with P-2012 & P-2032)
- Temp Range: 90°F - 160°F

NEW!



P-2022

OVERALL SIZE

18½"W x 23½"D x 28"H
18½"W x 23½"D x 3¼"H (with casters)

COMPARTMENT SIZE

- 3.5 cubic ft.
- 15½"W x 18¾"D x 21¼"H*
* (9½"H above and below the center shelf)

- Unit can be stacked (with P-2012 & P-2032)
- Temp Range: 90°F - 160°F

shown with solid door option

NEW!



P-2032

OVERALL SIZE

24"W x 25¼"D x 35½"H
24"W x 25¼"D x 40¾"H (with casters)

COMPARTMENT SIZE

- 7.5 cubic ft.
- 21"W x 21¾"D x 28¼"H
** (13½"H above and below the center shelf)

- Temp Range: 90°F - 160°F

shown with left door hinge option

warming cabinet features




Fluid Warmers

- Electro-thermal Radiant Heat Technology
- Safety coated interior
- Fully insulated
- 120 VAC
- No lint traps
- Heavy duty hardware
- Glass door and perimeter bumper
- 4-digit LED display
- Designed specifically for the warming of irrigation and intravenous fluids
- Individual temperature controls for irrigation fluids and intravenous fluids allow for precise temp settings for the proper fluid type
- Irrigation temperature adjusted from 90°F to 104°F (32°C to 65.5°C) or 98°F to 150°F (37°C to 65.5°C), depending on model.
- Intravenous temperature range adjusted from 98°F to 150°F (37°C to 65.5°C) 98°F to 104°F (37°C to 40°C), depending on model.
- Safety override feature prevents overheating
- Lockout feature
- Optional left hand door swing available
- Option of casters or fixed legs



Blanket Warmers

- Electro-thermal Radiant Heat Technology
- Safety coated interior
- Fully insulated
- 120 VAC
- No lint traps
- Heavy duty hardware
- No fans or other moving parts
- Blankets can be warmed to 160°F (93.3°C) or 200°F (93.3°C), depending on model.
- 4-digit LED display on Deluxe models
- 3 digit LED display on Standard models
- Perimeter bumper is optional on Deluxe models
- The P-2010-S is available with an optional caster stand or leg stand assembly, or can be used with P-2010-TC cart
- Safety override feature prevents overheating (Deluxe models only)
- Lockout feature (Deluxe models only)
- Optional left hand door swing available
- Option of casters or fixed legs



Elite Warmers

- Radiant Heat Technology
- White epoxy-coated steel interior insert & exterior casing
- Efficient, balanced heating system allows for low energy consumption and minimal heat loss
- Fully insulated
- 120 VAC
- No lint traps
- Door is fully gasketed and hinged on the right side of the unit
- No fans or other moving parts
- 4-digit L.E.D. display
- Easy, hands-free door release
- Single pane energy efficient e-coated glass window door allows inventory observation
- Adjustable temperature range of 90°F - 160°F (32°C - 71°C)
- Built-in speaker for audible feedback
- Built-in control button lock-out feature
- A warming shut-off system, separate from the electronic control, prevents overheating
- P-2220 and P-2240 includes a heated center shelf



Warranty for all Warming Cabinets

- One Year Service
- Three Years on Parts
- Lifetime Technical Support



fluid warming cabinets

Deluxe fluid warmers feature 4 digit LED display, window doors, programmable temperature control and interior lighting.

NEW!



12 1-liter bags or 16 1-liter bottles total capacity

NEW!



24 1-liter bags or 24 1-liter bottles total capacity



72 1-liter bags or 54 1-liter bottles total capacity

P-2112

OVERALL SIZE

18½"W x 23½"D x 22"H

COMPARTMENT SIZE

- 2.5 cubic ft.
- 15½"W x 18¾"D x 15¼"H

- **Capacity:** 12 1-liter bottles or 16 1-liter bags
- Unit can be stacked
- Temp Range: 90°F - 104°F adjustable injection mode
- Temp Range: 90°F - 150°F adjustable irrigation mode
- Glide out basket
- Casters (option)

P-2122

OVERALL SIZE

18½"W x 23½"D x 28"H

COMPARTMENT SIZE

- 3.5 cubic ft.
- 15½"W x 18¾"D x 21¼"H

- **Capacity:** 24 1-liter bottles or 24 1-liter bags
- Unit can be stacked
- Temp Range: 90°F - 104°F adjustable injection mode
- Temp Range: 90°F - 150°F adjustable irrigation mode
- Glide out basket (option)
- Casters (option)

P-2130

OVERALL SIZE (perimeter bumper included)

25¼"W x 35½"D x 41"H

COMPARTMENT SIZE

- 7.7 cubic ft.
- 18½"W x 26¾"D x 27"H

- **Capacity:** 54 1-liter bottles or 72 1-liter bags.
- Unit can be stacked
- Temp Range: 98°F - 104°F adjustable injection mode
- Temp Range: 98°F - 150°F adjustable irrigation mode
- Three epoxy-coated baskets with a capacity of 18 1-liters bottles or 24 1-liter bags per basket.
- 5" casters (standard)



P-2010-CB shown with the P-2010-S warmer

WARMING CABINETCASTER STAND

21¼"W x 29¾"D x 6¹³/₁₆"H

FEATURES

- Bumper
- Platform
- 4" diameter stainless steel casters with brakes.



elite series

Blanket warmers feature windowed door, temperature control and four digit LED display.



P-2205

OVERALL SIZE

18½"W x 20"D x 17"H

COMPARTMENT SIZE

- 1.5 cubic ft.
- 15½"W x 16¼"D x 10"H

- Unit can be stacked
- Temp Range: 90°F - 160°F



P-2210

OVERALL SIZE

- 18½"W x 23"D x 23"H

COMPARTMENT SIZE

- 2.5 cubic ft.
- 15½"W x 18¾"D x 15¼"H

- Unit can be stacked
- Temp Range: 90°F - 160°F



P-2220

OVERALL SIZE

- 18½"W x 23"D x 28"H

COMPARTMENT SIZE

- 3.5 cubic ft.
- 15½"W x 18¾"D x 21¼"H*
* (9⁹/₁₆"H above and below the center shelf)

- Unit can be stacked
- Temp Range: 90°F - 160°F
- Heated center shelf



P-2230

OVERALL SIZE

25"W x 25"D x 22"H

COMPARTMENT SIZE

- 4 cubic ft.
- 21"W x 21½"D x 15¼"H

- Unit can be stacked
- Temp Range: 90°F - 160°F



P-2240

OVERALL SIZE

- 24"W x 25½"D x 35½"H

COMPARTMENT SIZE

- 7.5 cubic ft.
- 21"W x 21¾"D x 28¼"H*
* (13¹/₈"H above and below the center shelf)

- Unit can be stacked
- Temp Range: 90°F - 160°F
- Heated center shelf



Pedigo warmers feature Radiant Heat Technology, a method for distributing a balance of heat throughout the cabinet, to assure accurate set-point temperatures. Fluid warmers also incorporate the use of a circulation fan to evenly distribute the warmed air to achieve and maintain accurate set-point temperatures. Pedigo fluid warmers have an accuracy of +0/-2°F for injection fluids and an accuracy of +0/-3°F for irrigation fluids. This ensures your fluids are kept at the proper temperature and will always be immediately available at or close to body temperature rather than room temperature without the hook-up time needed for catheter-warming systems.



blanket warming cabinets

Deluxe blanket warmers feature 4 digit LED display, window doors, control lock programming and auto time programming.



NEW!

P-2030-TC Transfer Cart

OVERALL SIZE

26"W x 33"D x 28"H

FEATURES

- Top shelf with 3-sided guardrail
- Bottom shelf with 4-sided rail
- 4" diameter stainless steel casters with brakes.

- 400 lbs. total weight capacity at 200 lbs. per shelf
- Stainless steel
- Compatible with the P-2032, P-2230 and P-2240 warming cabinets

P-2040 deluxe model

OVERALL SIZE (without bumper)

24"W x 34¹/₄"D x 72³/₄"H

COMPARTMENT SIZE

- 7.7 cubic ft. top compartment
- 19"W x 26¹/₄"D x 26³/₄"H
- 7.7 cubic ft. bottom compartment
- 19"W x 26¹/₄"D x 26³/₄"H

- Two compartments, each with individual controls
- Temp Range: 98°F - 200°F
- 5" casters

P-2055 deluxe model

OVERALL SIZE

32"W x 29¹/₄"D x 71"H

COMPARTMENT SIZE

- 20.6 cubic ft. both compartments
- 26¹/₂"W x 23³/₄"D x 56³/₄"H

- One compartment with two doors
- Temp Range: 98°F - 200°F
- Circulation fan to distribute heat
- 5" casters



fluid & blanket warming cabinets

Deluxe combination warmers feature 4 digit LED display, window doors, control lock programming and auto time programming.



72 1-liter bags or
54 1-liter bottles
total capacity

P-2140

OVERALL SIZE

- 24"W x 32¹/₂"D x 72³/₄"H

COMPARTMENT SIZE

- 7.7 cubic ft. blanket compartment
- 19"W x 27"D x 26³/₄" H
- 7.7 cubic ft. fluid compartment
- 19"W x 27"D x 26³/₄" H

- **Capacity:** 18 1-liter bottles or 24 1-liter bags.
- Fluid compartment has three epoxy-coated baskets each with a capacity of 18 1-liter bottles or 24 1-liter bags per basket.
- Separate temperature controls for each compartment
 - Temp Range Blankets: 98°F - 200°F
 - Temp Range Fluids: 98°F - 150°F
- Perimeter bumper included

24-36 1-liter bags or
30 1-liter bottles
total capacity

P-2147

OVERALL SIZE

- 30"W x 27⁷/₈"D x 74³/₄"H (feet - standard)
- 30"W x 27⁷/₈"D x 79¹/₈"H (caster option)

COMPARTMENT SIZE

- 30 liter fluid compartment
- 24³/₄"W x 24¹/₄"D x 14⁵/₈" H
- 16.4 cu. ft. blanket compartment
- 24³/₄"W x 24¹/₄"D x 24⁵/₈" H

- **Capacity:** 18 1-liter bottles or 24 1-liter bags.
- Fluid compartment has a maximum capacity of 30 1-liter bottles or 24-36 1-liter bags
- Separate temperature controls for each compartment
 - Temp Range Blankets: 90°F - 160°F
 - Temp Range IRR: 90°F - 150°F
 - Temp Range INJ: 90°F - 104°F

18 1-liter bags or
28 1-liter bottles
total capacity

P-2148

OVERALL SIZE

- 31"W x 22"D x 67¹/₄"H

COMPARTMENT SIZE

- 3.9 cu. ft. fluid compartment
- 26¹/₂"W x 17¹/₄"D x 14³/₄" H
- 8.7 cu. ft. blanket compartment
- 26¹/₂"W x 17¹/₄"D x 32³/₄" H

- Top compartment for fluids, lower compartment for blankets
- Fluid compartment has one easy access epoxy-coated basket with a maximum capacity of 18 1-liter bottles or 28 1-liter bags
- Separate temperature controls for each compartment
 - Temp Range Blankets: 98°F - 200°F
 - Temp Range Fluids: 98°F - 150°F
- 18" depth perfect for built-in OR applications