



ivNow[®]
individual warming pods



warming cabinets

blanket | elite series | fluid | combination





blanket warming cabinets

Warmers feature solid door and temperature control.



Shelf Dimensions
17"W x 27"D x 12 1/4"H

P-2010-TC Transfer Cart

OVERALL SIZE

23 1/4"W x 32 1/4"D x 43"H

FEATURES

- Ergonomic Push/Pull handles
- 4" casters with brake & swivel lock
- Stainless steel
- 300 lbs. total weight capacity at 100 lbs. per shelf
- Compatible with the P-2010-S and P-2110 warming cabinets



P-2010-S

OVERALL SIZE

16 1/2"W x 25 1/4"D x 21 1/2"H

COMPARTMENT SIZE

- 2.3 cubic ft.
- 13 1/4"W x 21 3/4"D x 14"H

- Ideal for countertop use
- Temp Range: 98°F - 200°F
- Unit can be stacked

NEW!



P-2012

OVERALL SIZE

18 1/2"W x 23 1/2"D x 22"H

COMPARTMENT SIZE

- 2.5 cubic ft.
- 15 1/2"W x 18 3/4"D x 15 1/4"H

- Ideal for countertop use
- Unit can be stacked (with P-2012 & P-2032)
- Temp Range: 90°F - 160°F

NEW!



P-2022

OVERALL SIZE

18 1/2"W x 23 1/2"D x 28"H
18 1/2"W x 23 1/2"D x 34 1/2"H (with casters)

COMPARTMENT SIZE

- 3.5 cubic ft.
- 15 1/2"W x 18 3/4"D x 21 1/4"H*
* (9 1/16"H above and below the center shelf)

- Unit can be stacked (with P-2012 & P-2032)
- Temp Range: 90°F - 160°F

NEW!



P-2032

OVERALL SIZE

24"W x 25 1/4"D x 35 1/2"H
24"W x 25 1/4"D x 42"H (with casters)

COMPARTMENT SIZE

- 7.5 cubic ft.
- 21"W x 21 3/4"D x 28 1/4"H
** (13 3/16"H above and below the center shelf)

- Temp Range: 90°F - 160°F



warming cabinet features




Fluid Warmers

- Electro-thermal Radiant Heat Technology
- Safety coated interior
- Fully insulated
- 120 VAC
- No lint traps
- Heavy duty hardware
- Glass door and perimeter bumper
- 4 digit LED display
- Designed specifically for the warming of irrigation and intravenous fluids
- Individual temperature controls for irrigation fluids and intravenous fluids allow for precise temp settings for the proper fluid type
- Irrigation temperature adjusted from 90°F to 104°F (32°C to 65.5°C) or 98°F to 150°F (37°C to 65.5°C), depending on model.
- Intravenous temperature range adjusted from 98°F to 150°F (37°C to 65.5°C) 98°F to 104°F (37°C to 40°C), depending on model.
- Built-in speaker for audible feedback
- Safety override feature prevents overheating
- Lockout feature
- Optional left hand door swing available
- Option of casters or fixed legs



Blanket Warmers

- Electro-thermal Radiant Heat Technology
- Safety coated interior
- Fully insulated
- 120 VAC
- No lint traps
- Heavy duty hardware
- No fans or other moving parts
- Blankets can be warmed to 160°F (93.3°C) or 200°F (93.3°C), depending on model.
- 4 digit LED display on Deluxe models
- 3 digit LED display on Standard models
- Perimeter bumper is optional on Deluxe models (excludes P-2055)
- The P-2010-S is available with an optional caster stand or leg stand assembly, or can be used with P-2010-TC cart
- Built-in speaker for audible feedback
- Safety override feature prevents overheating (Deluxe models only)
- Lockout feature (Deluxe models only)
- Optional left hand door swing available
- Option of casters or fixed legs



Elite Warmers

- Radiant Heat Technology
- White epoxy-coated steel interior insert & exterior casing
- Efficient, balanced heating system allows for low energy consumption and minimal heat loss
- Fully insulated
- 120 VAC
- No lint traps
- Door is fully gasketed and hinged on the right side of the unit
- No fans or other moving parts
- 4 digit L.E.D. display
- Easy, hands-free door release
- Single pane energy efficient e-coated glass window door allows inventory observation
- Adjustable temperature range of 90°F - 160°F (32°C - 71°C)
- Built-in speaker for audible feedback
- Built-in control button lock-out feature
- A warming shut-off system, separate from the electronic control, prevents overheating
- P-2220 and P-2240 includes a heated center shelf



Warranty for all Warming Cabinets

- One Year Service
- Three Years on Parts
- Lifetime Technical Support



fluid warming cabinets

Deluxe fluid warmers feature 4 digit LED display, window doors, programmable temperature control and interior lighting.

NEW!



12 1-liter bags or 16 1-liter bottles total capacity

P-2112

OVERALL SIZE

18½"W x 23½"D x 22"H

COMPARTMENT SIZE

- 2.5 cubic ft.
- 15½"W x 18¾"D x 15¼"H

- **Capacity:** 12 1-liter bottles or 16 1-liter bags
- Unit can be stacked
- Temp Range: 90°F - 104°F adjustable injection mode
- Temp Range: 90°F - 150°F adjustable irrigation mode
- Glide out basket
- WarmWatch (option)
- Casters (option)

NEW!



24 1-liter bags or 24 1-liter bottles total capacity

P-2122

OVERALL SIZE

18½"W x 23½"D x 28"H

COMPARTMENT SIZE

- 3.5 cubic ft.
- 15½"W x 18¾"D x 21¼"H

- **Capacity:** 24 1-liter bottles or 24 1-liter bags
- Unit can be stacked
- Temp Range: 90°F - 104°F adjustable injection mode
- Temp Range: 90°F - 150°F adjustable irrigation mode
- Glide out basket (option)
- Casters (option)
- WarmWatch (option)



72 1-liter bags or 54 1-liter bottles total capacity

P-2130

OVERALL SIZE (perimeter bumper included)

25¼"W x 35½"D x 41"H

COMPARTMENT SIZE

- 7.7 cubic ft.
- 18½"W x 26¾"D x 27"H

- **Capacity:** 54 1-liter bottles or 72 1-liter bags.
- Unit can be stacked
- Temp Range: 98°F - 104°F adjustable injection mode
- Temp Range: 98°F - 150°F adjustable irrigation mode
- Three epoxy-coated baskets with a capacity of 18 1-liters bottles or 24 1-liter bags per basket.
- 5" casters (standard)



P-2010-CB shown with the P-2010-S warmer

WARMING CABINETCASTER STAND

21¼"W x 29⅜"D x 6¹³/₁₆"H

FEATURES

- Bumper
- Platform
- 4" diameter stainless steel casters with brakes.



elite series

Blanket warmers feature windowed door, temperature control and four digit LED display.



P-2205

OVERALL SIZE

18½"W x 20"D x 17"H

COMPARTMENT SIZE

- 1.5 cubic ft.
- 15½"W x 16¼"D x 10"H

- Unit can be stacked
- Temp Range: 90°F - 160°F



P-2210

OVERALL SIZE

- 18½"W x 23"D x 23"H

COMPARTMENT SIZE

- 2.5 cubic ft.
- 15½"W x 18¾"D x 15¼"H

- Unit can be stacked
- Temp Range: 90°F - 160°F



P-2220

OVERALL SIZE

- 18½"W x 23"D x 28"H

COMPARTMENT SIZE

- 3.5 cubic ft.
- 15½"W x 18¾"D x 21¼"H*
* (9⁹/₁₆"H above and below the center shelf)

- Unit can be stacked
- Temp Range: 90°F - 160°F
- Heated center shelf



P-2230

OVERALL SIZE

25"W x 25"D x 22"H

COMPARTMENT SIZE

- 4 cubic ft.
- 21"W x 21½"D x 15¼"H

- Unit can be stacked
- Temp Range: 90°F - 160°F



P-2240

OVERALL SIZE

- 24"W x 25½"D x 35½"H

COMPARTMENT SIZE

- 7.5 cubic ft.
- 21"W x 21¾"D x 28¼"H*
* (13⁵/₁₆"H above and below the center shelf)

- Unit can be stacked
- Temp Range: 90°F - 160°F
- Heated center shelf



Pedigo warmers feature Radiant Heat Technology, a method for distributing a balance of heat throughout the cabinet, to assure accurate set-point temperatures. Fluid warmers also incorporate the use of a circulation fan to evenly distribute the warmed air to achieve and maintain accurate set-point temperatures. Pedigo fluid warmers have an accuracy of +0/-2°F for injection fluids and an accuracy of +0/-3°F for irrigation fluids. This ensures your fluids are kept at the proper temperature and will always be immediately available at or close to body temperature without the hook-up time needed for catheter-warming systems.



blanket warming cabinets

Deluxe blanket warmers feature 4 digit LED display, window doors, control lock programming and auto time programming.



NEW!

P-2030-TC Transfer Cart

OVERALL SIZE

26"W x 33"D x 28"H

FEATURES

- Top shelf with 3-sided guardrail
- Bottom shelf with 4-sided rail
- 4" diameter stainless steel casters with brakes.

- 400 lbs. total weight capacity at 200 lbs. per shelf
- Stainless steel
- Compatible with the P-2032, P-2230 and P-2240 warming cabinets

P-2040 deluxe model

OVERALL SIZE (without bumper)

24"W x 34¼"D x 72¾"H

COMPARTMENT SIZE

- 7.7 cubic ft. top compartment
- 19"W x 26¼"D x 26¾"H
- 7.7 cubic ft. bottom compartment
- 19"W x 26¼"D x 26¾"H

- Two compartments, each with individual controls
- Temp Range: 98°F - 200°F
- 5" casters

P-2055 deluxe model

OVERALL SIZE

32"W x 29¼"D x 71"H

COMPARTMENT SIZE

- 20.6 cubic ft. both compartments
- 26½"W x 23¾"D x 56¾"H

- One compartment with two doors
- Temp Range: 98°F - 200°F
- 5" casters



fluid & blanket warming cabinets

Deluxe combination warmers feature 4 digit LED display, window doors, control lock programming and auto time programming.



72 1-liter bags or
54 1-liter bottles
total capacity

P-2140

OVERALL SIZE

- 24"W x 32½"D x 72¾"H

COMPARTMENT SIZE

- 7.7 cubic ft. blanket compartment
- 19"W x 27"D x 26¾" H
- 7.7 cubic ft. fluid compartment
- 19"W x 27"D x 26¾" H

- **Capacity:** 18 1-liter bottles or 24 1-liter bags.
- Fluid compartment has three epoxy-coated baskets each with a capacity of 18 1-liters bottles or 24 1-liter bags per basket.
- Separate temperature controls for each compartment
 - Temp Range Blankets: 98°F - 200°F
 - Temp Range Fluids: 98°F - 150°F
- Perimeter bumper included

24-36 1-liter bags or
30 1-liter bottles
total capacity

P-2147

OVERALL SIZE

- 30"W x 28½"D x 68"H (feet - standard)
- 30"W x 28½"D x 75"H (caster option)

COMPARTMENT SIZE

- 30 liter fluid compartment
- 26½"W x 23¾"D x 15"H
- 13 cu. ft. blanket compartment
- 26¾"W x 23¾"D x 36"H

- **Capacity:** 18 1-liter bottles or 24 1-liter bags.
- Fluid compartment has a maximum capacity of 30 1-liter bottles or 24-36 1-liter bags
- Separate temperature controls for each compartment
 - Temp Range Blankets: 90°F - 160°F
 - Temp Range IRR: 90°F - 150°F
 - Temp Range INJ: 90°F - 104°F
- WarmWatch standard

24 1-liter bags or
20 1-liter bottles
total capacity

P-2150

OVERALL SIZE

- 30"W x 19¾"D x 75"H

COMPARTMENT SIZE

- 3.9 cu. ft. fluid compartment
- 24¼"W x 17" D x 15"H
- 9.39 cu. ft. blanket compartment
- 24¼"W x 17"D x 36"H

- Top compartment for fluids, lower compartment for blankets
- Fluid compartment has a maximum capacity of 24 1-liter bottles or 20 1-liter bags
- Separate temperature controls for each compartment
 - Temp Range Blankets: 90°F - 160°F
 - Temp Range IRR: 90°F - 150°F
 - Temp Range INJ: 90°F - 104°F
- WarmWatch standard