



Industry First

- Cart doors feature polycarbonate scratch-resistant windows that allow the staff to determine the status of the cart at a glance.
- Aluminum and stainless steel construction.

Design

- Integrated body, floor and doors increases overall cart rigidity.
- Inside floor is sloped 1½° to the rear of cart to contain fluids.
- High temp, impact resistant bumper is mounted directly to the cart body to reduce overall footprint.
- Roll-out shelves with two position latch mechanism safely locks the shelf in or out.
- Cart is designed to quickly drain during cart washing to minimize residual water.

Ergonomic

- Glass-filled polymer handle system with integrated door catch mechanism.
- Polymer handle is cooler to the touch after cart washing.
- Overall weight of cart reduced.
- Horizontal mounted paddle latches.



RCC-242 Inside Clearance Dimensions:
23½"D x 26¾"H x 37¼"W



RCC-242 Outside Dimensions:
27½"D x 41½"H x 45½"W (top) / 46¼"W (bottom)

Shelving Configurations

RCC-233-WS..... Wire shelf, for RCC-233 and RCC-256-MS.

RCC-233-WSRO .. Roll-out wire shelf, with (2) position spring loaded shelf lock. Shelf locks in storage and fully extended position for RCC-233 and RCC-256-MS.

RCC-235-WS..... Wire shelf, for RCC-235.

RCC-235-WSRO .. Roll-out wire shelf, with (2) position spring loaded shelf lock. Shelf locks in storage and fully extended position, for RCC-235.

RCC-242-WS..... Wire shelf, for RCC-242 and RCC-245.

RCC-242-WSRO .. Roll-out wire shelf, with (2) position spring loaded shelf lock. Shelf locks in storage and fully extended position, for RCC-242 and RCC-245.




rev • o • lu • tion™

closed surgical case cart
Covered by US Patent D707,912 S2



Custom rev•o•lu•tion™ carts engineered to customer specifications available upon request.





RCC-233
Overall outside dimensions:
29"W x 27½"D x 59"H
Usable Interior Space
20"W x 23½"D x 44¾"H

Single door, with scratch and impact resistant clear polycarbonate windows; glass-filled polymer push handles on each end; re • volve™ 6" diameter, maintenance-free, high-temp, engineered thermoplastic casters, two swivel and two with direction lock.



RCC-235
Overall outside dimensions:
36"W x 27½"D x 59"H
Usable Interior Space
27"W x 23½"D x 44¾"H

Double door, with scratch and impact resistant clear polycarbonate windows; glass-filled polymer push handles on each end; re • volve™ 6" diameter, maintenance-free, high-temp, engineered thermoplastic casters, two swivel and two with direction lock.



RCC-242
Overall outside dimensions:
46¼"W x 27½"D x 42"H
Usable Interior Space
37¼"W x 23½"D x 27¾"H

Double door, with scratch and impact resistant clear polycarbonate windows; glass-filled polymer push handles on each end; re • volve™ 6" diameter, maintenance-free, high-temp, engineered thermoplastic casters, two swivel and two with direction lock.



RCC-245
Overall outside dimensions:
46¼"W x 27½"D x 59"H
Usable Interior Space
37¼"W x 23½"D x 44¾"H

Double door, with scratch and impact resistant clear polycarbonate windows; glass-filled polymer push handles on each end; re • volve™ 6" diameter, maintenance-free, high-temp, engineered thermoplastic casters, two swivel and two with direction lock.



RCC-256-MS
Overall outside dimensions:
29"W x 27½"D x 42"H
Usable Interior Space
20"W x 23½"D x 27¾"H

Single door, with scratch and impact resistant clear polycarbonate window; glass-filled polymer push handles on each end; re • volve™ 6" diameter, maintenance-free, high-temp, engineered thermoplastic casters, two swivel and two with direction lock.

Cool Touch Handles

Ergonomic, polymer handle is cooler to the touch than stainless steel after emerging from the cart washer. No need for gloves or towels to wrap around hot metal handles. For convenience and ease of access, the glass-filled polymer handle system is integrated with a door catch mechanism.



Handles

Integrated Door Catch

Ergonomic Door Latches
Mounted horizontally.

Windowed Doors
Rubber gasket seals windows & interior contents.

The rev • o • lu • tion™ closed case cart is ergonomically designed to be lightweight and easy to handle, requiring less push/pull force than standard case carts. Unique features make the cart safe and easy to use.

Adjustable Door Hinge
For proper alignment.



2 Position Shelf Lock

Shelf Lock

The new two position, spring loaded arm mechanism securely locks the shelf in the extended or retracted position. With the shelf fixed in the extended position, staff can easily and safely load the cart without movement from the shelf.

Aluminum Powder-Coated Doors
Custom high-temp, chip resistant powder-coat finish.

Direction Lock

Cart features two pedal activated swivel lock casters located at diagonal corners. Direction lock is integrated into the saddle of the caster. This improvement allows for upgrades or caster replacement to take place in the field. Caster is bolt mounted.



Direction Lock

Floor Sloped Toward Rear
1½° slope for containment of fluid.



re • volve™ caster

The re • volve™ caster

New maintenance-free re • volve™ caster is a proprietary component of Pedigo Products, Inc. The caster is made from engineered thermoplastic. Rated to 280° Fahrenheit, this high temp caster features four precision bearings in each caster - best in the industry. Twin sets of precision stainless steel sealed ball bearings in the axle and swivel improves cart handling, maneuverability and reduces the overall push/pull force by 32%.